

# DATASHEET

## Coil nailer CN45

CN45 Coil nailer							
	<b>FEATURES</b> <ul style="list-style-type: none"> <li>* Light weight</li> <li>* Drives both conical wire welded and plastic sheet collated nails without any adjustment</li> <li>* Adjustable firing mode, single fire or bump fire</li> <li>* Depth control dial, nail depth is easily adjusted</li> <li>* Plastic carrying case included</li> </ul>						
	<b>APPLICATIONS</b> <ul style="list-style-type: none"> <li>* Sub-flooring</li> <li>* Fencing</li> <li>* Wall sheathing and roof sheathing</li> <li>* Fastening gypsum board, decorative board and other interior boards</li> </ul>						
SPECIFICATIONS							
Weight Dimensions Load capacity  Maximum allowable pressure Recommended pressure range Actuation mode	1.60 kg 248 x 108 x 260 mm 400 nails (conical wire welded nails) 200 nails (plastic sheet collated nails) 8.3bar 5bar to 7bar Contact/Single-sequential actuation						
FASTENERS							
Nail Length  Shank Diameter  Head Diameter 	15° conical wire welded nails and flat plastic sheet collated nails  <table border="1"> <tr> <td>Length</td> <td>25~50 mm</td> </tr> <tr> <td>Shank</td> <td>1.59~2.1 mm</td> </tr> <tr> <td>Head</td> <td>3.5~5.0 mm</td> </tr> </table>	Length	25~50 mm	Shank	1.59~2.1 mm	Head	3.5~5.0 mm
Length	25~50 mm						
Shank	1.59~2.1 mm						
Head	3.5~5.0 mm						