

DATASHEET

Coil nailer CN90B

CN90B Coil nailer																			
	FEATURES <ul style="list-style-type: none"> * New design → more power * Depth control dial, nail depth is easily adjusted * Adjustable firing mode, single fire or bump fire 																		
	APPLICATIONS <ul style="list-style-type: none"> * Floor and wall framing * Roof and wall sheathing * Fencing * Pallets, drums and wooden boxes 																		
SPECIFICATIONS																			
Weight Dimensions Load capacity Maximum allowable pressure Recommended pressure range Actuation mode	3.9 kg 360 x 312 x 141 mm 200~300 nails 8.3bar 5bar to 7bar Contact actuation																		
FASTENERS																			
 <p>15° Flat wire welded coil nails</p>	<table border="1"> <thead> <tr> <th>Nail Length</th> <th>Shank Diameter</th> <th>Head Diameter</th> <th></th> </tr> </thead> <tbody> <tr> <td>  </td> <td>  <p>smooth screw and ring shank</p> </td> <td>  </td> <td> 15° flat wire welded coil nails </td> </tr> <tr> <td></td> <td></td> <td></td> <td> <table border="1"> <tbody> <tr> <td>Length</td> <td>50~90 mm</td> </tr> <tr> <td>Shank</td> <td>2.5~3.8 mm</td> </tr> <tr> <td>Head</td> <td>6.0~8.0 mm</td> </tr> </tbody> </table> </td> </tr> </tbody> </table>	Nail Length	Shank Diameter	Head Diameter			 <p>smooth screw and ring shank</p>		15° flat wire welded coil nails				<table border="1"> <tbody> <tr> <td>Length</td> <td>50~90 mm</td> </tr> <tr> <td>Shank</td> <td>2.5~3.8 mm</td> </tr> <tr> <td>Head</td> <td>6.0~8.0 mm</td> </tr> </tbody> </table>	Length	50~90 mm	Shank	2.5~3.8 mm	Head	6.0~8.0 mm
Nail Length	Shank Diameter	Head Diameter																	
	 <p>smooth screw and ring shank</p>		15° flat wire welded coil nails																
			<table border="1"> <tbody> <tr> <td>Length</td> <td>50~90 mm</td> </tr> <tr> <td>Shank</td> <td>2.5~3.8 mm</td> </tr> <tr> <td>Head</td> <td>6.0~8.0 mm</td> </tr> </tbody> </table>	Length	50~90 mm	Shank	2.5~3.8 mm	Head	6.0~8.0 mm										
Length	50~90 mm																		
Shank	2.5~3.8 mm																		
Head	6.0~8.0 mm																		