

# DATASHEET

## Coil nailer CN565B

CN565B Coil nailer										
	<b>FEATURES</b> <ul style="list-style-type: none"> <li>* Light weight</li> <li>* Drives both flat wire welded and plastic sheet collated nails without any adjustment</li> <li>* Adjustable firing mode, single fire or bump fire</li> <li>* Depth control dial, nail depth is easily adjusted</li> <li>* Plastic carrying case included</li> </ul>									
	<b>APPLICATIONS</b> <ul style="list-style-type: none"> <li>* Siding (hardboard and cement)</li> <li>* Sheathing, fencing and sub-flooring</li> <li>* Roof decking</li> <li>* Exterior deck and trim</li> <li>* Furring and strapping</li> </ul>									
SPECIFICATIONS										
Weight Dimensions Load capacity  Maximum allowable pressure Recommended pressure range Actuation mode	2.50 kg 320 x 130 x 273 mm 250~400 nails (flat wire welded nails) 200 nails (plastic sheet collated nails) 8.3bar 5bar to 7bar Contact/Single-sequential actuation									
FASTENERS										
<table border="0"> <tr> <td style="text-align: center;"> <b>Nail Length</b>            Plastic Sheet            32mm            Wire Weld            45mm            65mm         </td> <td style="text-align: center;"> <b>Shank Diameter</b>            2.3mm to 2.5mm         </td> <td style="text-align: center;"> <b>Head Diameter</b>            5.0mm to 6.0mm         </td> </tr> </table>	<b>Nail Length</b> Plastic Sheet 32mm Wire Weld 45mm 65mm	<b>Shank Diameter</b> 2.3mm to 2.5mm	<b>Head Diameter</b> 5.0mm to 6.0mm	15° flat wire welded nails and flat plastic sheet collated nails <table border="0"> <tr> <td style="text-align: right;">Length</td> <td>45~65 mm (wire welded) 32~65 mm (plastic collated)</td> </tr> <tr> <td style="text-align: right;">Shank</td> <td>2.3~2.5 mm</td> </tr> <tr> <td style="text-align: right;">Head</td> <td>5.0~6.0 mm</td> </tr> </table>	Length	45~65 mm (wire welded) 32~65 mm (plastic collated)	Shank	2.3~2.5 mm	Head	5.0~6.0 mm
<b>Nail Length</b> Plastic Sheet 32mm Wire Weld 45mm 65mm	<b>Shank Diameter</b> 2.3mm to 2.5mm	<b>Head Diameter</b> 5.0mm to 6.0mm								
Length	45~65 mm (wire welded) 32~65 mm (plastic collated)									
Shank	2.3~2.5 mm									
Head	5.0~6.0 mm									