

# DATASHEET

## Roofing Coil nailer CRN45A

CRN45A Roofing coil nailer																		
	<b>FEATURES</b> <ul style="list-style-type: none"> <li>* Powerful</li> <li>* Light weight</li> <li>Adjustable firing mode, single fire or bump fire</li> <li>* Depth control dial, nail depth is easily adjusted</li> <li>* Plastic carrying case included</li> </ul>																	
	<b>APPLICATIONS</b> <ul style="list-style-type: none"> <li>* Fastening asphalt and fiberglass shingles</li> <li>* Siding installation</li> <li>* Fastening lath wire on plywood</li> <li>* Wooden box assembly</li> <li>* Thin metal applications</li> </ul>																	
SPECIFICATIONS																		
Weight Dimensions Load capacity Maximum allowable pressure Recommended pressure range Actuation mode	2.58 kg 313 x 116 x 271 mm 120 nails 8.3bar 5bar to 7bar Contact/Single-sequential actuation																	
FASTENERS																		
<table border="0"> <tr> <td>Shank Type</td> <td>Ring</td> <td>Nail Length</td> <td>Shank Diameter</td> <td>Head Diameter</td> <td rowspan="2">15° wire welded coil roofing nails</td> </tr> <tr> <td>Smooth</td> <td>Ring</td> <td>19mm - 45mm</td> <td>3.05mm</td> <td>10.5mm</td> </tr> </table>	Shank Type	Ring	Nail Length	Shank Diameter	Head Diameter	15° wire welded coil roofing nails	Smooth	Ring	19mm - 45mm	3.05mm	10.5mm	<table border="0"> <tr> <td>Length</td> <td>19~45 mm</td> </tr> <tr> <td>Shank</td> <td>3.05 mm</td> </tr> <tr> <td>Head</td> <td>10.5 mm</td> </tr> </table>	Length	19~45 mm	Shank	3.05 mm	Head	10.5 mm
Shank Type	Ring	Nail Length	Shank Diameter	Head Diameter	15° wire welded coil roofing nails													
Smooth	Ring	19mm - 45mm	3.05mm	10.5mm														
Length	19~45 mm																	
Shank	3.05 mm																	
Head	10.5 mm																	