











# DATASHEET

## Framing nailer SRN9021

SRN9021 Framing nailer																												
	<b>FEATURES</b> <ul style="list-style-type: none"> <li>* Powerful</li> <li>* Big load capacity</li> <li>* Comfortable rubber grip</li> </ul>																											
	<b>APPLICATIONS</b> <ul style="list-style-type: none"> <li>* Floor and wall framing</li> <li>* Window build-up</li> <li>* Wall sheathing</li> <li>* Roofing</li> </ul>																											
SPECIFICATIONS																												
Weight Dimensions Load capacity Maximum allowable pressure Recommended pressure range Actuation mode	3.59 kg 554 x 108 x 340 mm 64~70 nails 8.3bar 5bar to 7bar Contact /Sequential actuation																											
FASTENERS																												
<table border="0"> <tr> <td colspan="3">Shank Type</td> <td colspan="2">Nail Length</td> <td>Shank Diameter</td> <td>Head Diameter</td> </tr> <tr> <td>Smooth</td> <td>Screw</td> <td>Ring</td> <td>50mm</td> <td>83mm</td> <td>2.87mm ~ 3.33mm</td> <td>5.8mm ~ 7.2mm</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	Shank Type			Nail Length		Shank Diameter	Head Diameter	Smooth	Screw	Ring	50mm	83mm	2.87mm ~ 3.33mm	5.8mm ~ 7.2mm								21° plastic collated strip nails  <table border="1"> <tr> <td>Length</td> <td>50~90 mm</td> </tr> <tr> <td>Shank</td> <td>2.8~3.33 mm</td> </tr> <tr> <td>Head</td> <td>5.8~7.2 mm</td> </tr> </table>	Length	50~90 mm	Shank	2.8~3.33 mm	Head	5.8~7.2 mm
Shank Type			Nail Length		Shank Diameter	Head Diameter																						
Smooth	Screw	Ring	50mm	83mm	2.87mm ~ 3.33mm	5.8mm ~ 7.2mm																						
																												
Length	50~90 mm																											
Shank	2.8~3.33 mm																											
Head	5.8~7.2 mm																											