

DATASHEET

Coil nailer CN565X

CN565X Coil nailer										
	FEATURES <ul style="list-style-type: none"> * Light weight. * Drives both flat wire welded and plastic sheet collated nails without any adjustment. * Anti-double fire trigger. To move between bump fire and single fire mode no adjustment to the tool is necessary. * Depth control dial, nail depth is easily adjusted. * Plastic carrying case included. 									
	APPLICATIONS <ul style="list-style-type: none"> * Siding (hardboard and cement) * Sheathing, fencing and sub-flooring * Roof decking * Exterior deck and trim * Furring and strapping 									
SPECIFICATIONS										
Weight Dimensions Load capacity Maximum allowable pressure Recommended pressure range Actuation mode	2.58 kg 315 x 128 x 306 mm 225~300 nails (flat wire welded nails) 200 nails (plastic sheet collated nails) 8.3bar 5bar to 7bar Contact/Single-sequential actuation									
FASTENERS										
<table border="0"> <tr> <td style="text-align: center;"> Nail Length  </td> <td style="text-align: center;"> Shank Diameter  </td> <td style="text-align: center;"> Head Diameter  </td> </tr> </table>	Nail Length 	Shank Diameter 	Head Diameter 	15° flat wire welded nails and flat plastic sheet collated nails <table border="1"> <tr> <td>Length</td> <td>45~65 mm (wire welded) 32~65 mm (plastic collated)</td> </tr> <tr> <td>Shank</td> <td>2.3~2.5 mm</td> </tr> <tr> <td>Head</td> <td>5.0~6.0 mm</td> </tr> </table>	Length	45~65 mm (wire welded) 32~65 mm (plastic collated)	Shank	2.3~2.5 mm	Head	5.0~6.0 mm
Nail Length 	Shank Diameter 	Head Diameter 								
Length	45~65 mm (wire welded) 32~65 mm (plastic collated)									
Shank	2.3~2.5 mm									
Head	5.0~6.0 mm									