


DATA SHEET

20V Cordless Framing Nailer LD34100

LD34100						
	FEATURES <ul style="list-style-type: none"> ✓ Brushless motor technology ✓ Select fire mode button ✓ Adjustable nail depth ✓ Belt hook ✓ Drives up to 750 nails/charge ✓ Plastic carrying case included ✓ 2 x 20 V 4.0 Ah lithium-ion batteries & 1 x 2A charger included 					
	APPLICATIONS <ul style="list-style-type: none"> • Floor and wall framing • Window build-up • Wall sheathing • Roofing 					
SPECIFICATIONS						
Weight (w/o battery) Dimensions (w/o battery) Load capacity Firing speed Recommended pressure range Actuation mode Battery Impact power	4.2 kg 370 x 340 x 131 mm 50 nails Up to 90 nails/min 5~8 bar (adjustable through air valve) Contact/sequential actuation 20 V 4.0 Ah lithium-ion battery & 2A charger 100~120J					
FASTENERS						
 <p>Paper collation</p>	34° paper tape collated strip nails					
	<table> <tr> <td>Length</td><td>50~100 mm (Ring shank up to 100 mm in soft wood)</td></tr> <tr> <td>Shank</td><td>2.87~3.76 mm</td></tr> <tr> <td>Head</td><td>6.8~7.2 mm</td></tr> </table>	Length	50~100 mm (Ring shank up to 100 mm in soft wood)	Shank	2.87~3.76 mm	Head
Length	50~100 mm (Ring shank up to 100 mm in soft wood)					
Shank	2.87~3.76 mm					
Head	6.8~7.2 mm					